



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0
Issued: 20 July 2009

Page: 1 of 5
MSDS No: 610

CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC CRITERIA

1. Identification of the substance/preparation and company

Product:

Sikafloor 264T Part A

Recommended use:

High build epoxy coating

Manufacturer/supplier information:

Manufacturer/supplier:	Sika Australia Pty Ltd
Street/postbox:	55 Elizabeth Street
Town/city and Post Code:	WETHERILL PARK NSW 2164
Country:	AUSTRALIA
Phone:	(02) 9725 1145
Fax:	(02) 9725 3330
General information	Operations Manager

Emergency information phone: 1800 033 111

2. Composition/information on ingredients

Chemical characterization:

Filled modified epoxy resin.

Hazardous ingredients:

Ingredient	CAS No	Concentration
Reaction product: bisphenol A-(epichlorohydrin)	25068-38-6	30-60%
Reaction product: bisphenol F-(epichlorohydrin)	9003-36-5	1-10%
Oxirane, mono(C12-14-alkyloxy)methyl derivatives	68609-97-2	1-10%
Benzyl alcohol	100-51-6	1 – 2%
Ethanol	64-17-5	1 -2%

3. Hazard identification

Hazard Category:

Xi Irritant

Risk Phrase(s)

R36/38:	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long term adverse effects in aquatic environment.

Safety Phrase(s):

S24/25	Avoid contact with skin and eyes.
S36/37/38:	Wear suitable protective clothing, gloves and eye/face protection.
S61	Avoid release to environment.

4. First-aid measures

Inhalation:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0

Page: 2 of 5

Issued: 20 July 2009

MSDS No: 610

Skin contact:

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact:

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion:

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766). Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician:

Treat symptomatically.

5. Fire-fighting measures

Specific hazards:

Combustible material. In the event of fire oxides of carbon, halogenated compounds and metal oxides can be released.

Special protective precautions and equipment:

On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable extinguishing media:

If material is involved in a fire use, foam, dry chemical and carbon dioxide.
Do not use water fog.

6. Accidental release measures

Small Spills:

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (sand, earth). Collect and seal in properly labelled containers or drums for disposal.

Large spills:

Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Shut off possible sources of ignition. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

7. Handling and storage

Handling:

Avoid skin and eye contact.

Storage:

Store in a cool, dry, well-ventilated place and out of direct sunlight, frost, atmospheric moisture and water. Store away from oxidizing agents. Keep containers closed when not in use - check regularly for leaks. Keep away from food, beverages and animal feedstock.

8. Exposure controls/personal protection

National occupational exposure limits:

No value assigned for this specific material by the NOHSC Australia.



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0

Page: 3 of 5

Issued: 20 July 2009

MSDS No: 610

However for:

	TWA		STEL		CARCINOGEN	NOTICES
	ppm	mg/m ³	ppm	mg/m ³	CATEGORY	
Epichlorohydrin	2	7.6				Sk
Ethanol	1000	1880				

Biological Limit Values:

As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures:

Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Natural ventilation should be adequate under normal use conditions.

Personal protection equipment:

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Due to variations in glove construction and local conditions, the user should make an assessment of the appropriate gloves to use. Wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. Physical and chemical properties

Appearance:

Physical state: Thixotropic Liquid
Colour: Various
Odour: Characteristic

Data relevant to safety:

Solubility: insoluble
Density(20 °C): 1.41 g/cm³
Vapour Pressure (20 °C): N Av
Flash Point (°C): 86
Flammability Limits (%): N Av
Autoignition Temperature (°C): N Av

(Typical values only - consult specification sheet)

N Av = Not available

10. Stability and reactivity

Chemical stability:

This material is thermally stable when stored and used as directed.

Conditions to avoid:

Avoid possible sources of ignition.

Materials to avoid:

Oxidizing agents.

Hazardous decomposition products:

Oxides of carbon, smoke and other toxic fumes.



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0
Issued: 20 July 2009

Page: 4 of 5
MSDS No: 610

Hazardous reactions:

Under normal conditions and storage hazardous decomposition products should not be produced.

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects:

Inhalation: No known effects or critical hazards.

Skin contact: Irritating to skin and may cause sensitization by skin contact..

Eye contact: An eye irritant.

Ingestion:

Irritating to mouth throat and stomach.

Long Term Effects:

No information available for the product.

Acute toxicity / Chronic toxicity:

Oxirane, mono(C12-14-alkyloxy)methyl derivatives

LD50 Oral (rat) 17100mg/kg

12. Ecological information

Avoid contaminating waterways.

Ecotoxicity:

No information available.

Persistence and degradability:

No information available.

Mobility:

No information available.

13. Disposal considerations

Refer to State/Territory Land Waste Management Authority.

14. Transport information

ADG/ADR/RID

UN. No.	3082
Dangerous Goods Class	9
Packing Group	III
Proper Shipping Name:	Environmentally hazardous substance liquid, n.o.s

IMDG

UN. No.	3082
Dangerous Goods Class	9
Packing Group	III
Proper Shipping Name:	Environmentally hazardous substance liquid, n.o.s



Safety Data Sheet

According to NOHSC:2011(2003)

Version: 1.0

Page: 5 of 4

Issued: 20 July 2009

MSDS No: 610

IATA

UN. No.	3082
Dangerous Goods Class	9
Packing Group	III
Proper Shipping Name:	Environmentally hazardous substance liquid, n.o.s

15. Regulatory information

Poisons Schedule (Aust):

This material is Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other information

Reason(s) For Issue: New product

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: www.sika.com.au

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.

Material Safety Data Sheet



1. Identification of the material and supplier

Names

Product name : Sikafloor 264, Comp. B
ADG : Corrosive liquid, n.o.s.

Supplier

Supplier/Manufacturer : Sika Australia Pty. Ltd.
55 Elizabeth Street
(Locked Bag 482 BDC)
Wetherill Park, NSW 2164
Australia

Telephone no. : +61 2 9725 11 45

Fax no. : +61 2 9725 33 30

Emergency telephone number : +61 1800 033 111

Use of the substance/preparation : Chemical product for construction and industry

2. Hazards identification

Classification : Xn; R20/22
C; R35
R43
N; R51/53

Risk phrases : R20/22- Harmful by inhalation and if swallowed.
R35- Causes severe burns.
R43- May cause sensitization by skin contact.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases : S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39- Wear suitable protective clothing, gloves and eye/face protection.
S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

Statement of hazardous/dangerous nature : HAZARDOUS SUBSTANCE. DANGEROUS GOODS.

3. Composition/information on ingredients

Mixture : Yes.

benzyl alcohol	100-51-6	30 - <60
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	10 - <30
m-phenylenebis(methylamine)	1477-55-0	10 - <30
reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	10 - <30
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	1 - <10

Other ingredients, determined not to be hazardous according to NOHSC criteria, and not dangerous according to the ADG Code, make up the product concentration to 100%.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

First aid measures

Inhalation

: Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Ingestion

: Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

: Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5 . Fire-fighting measures

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

In a fire or if heated, a pressure increase will occur and the container may burst.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hazardous combustion products

: Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

Occupational exposure limits

Ingredient name

m-phenylenebis(methylamine)

Exposure limits

NOHSC (Australia, 8/2005). Absorbed through skin.

PEAK: 0.1 mg/m³ 15 minute(s).

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Exposure controls

Engineering measures

- : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

8 . Exposure controls/personal protection

- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

- Physical state** : Liquid.
- Density** : 0.96 to 1.06 g/cm³ [23°C (73.4°F)]

10 . Stability and reactivity

- Stability** : The product is stable.
- Conditions to avoid** : Avoid release to the environment. Refer to special instructions/safety data sheet.
- Materials to avoid** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11 . Toxicological information

Potential acute health effects

- Inhalation** : Harmful by inhalation. May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.
- Skin contact** : Severely corrosive to the skin. Causes severe burns. May cause sensitization by skin contact.
- Eye contact** : Severely corrosive to the eyes. Causes severe burns.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure	
benzyl alcohol	LD50 Dermal	Rabbit	2000 mg/kg	-	
	LD50 Intra-arterial	Rat	441 mg/kg	-	
	LD50 Intraperitoneal	Mouse	650 mg/kg	-	
	LD50 Intraperitoneal	Rat	400 mg/kg	-	
	LD50 Intravenous	Mouse	324 mg/kg	-	
	LD50 Intravenous	Rat	53 mg/kg	-	
	LD50 Oral	Rat	1660 mg/kg	-	
	LD50 Oral	Rat	1230 mg/kg	-	
	LD50 Oral	Mouse	1360 mg/kg	-	
	LD50 Oral	Rat	1.5 mL/kg	-	
	LD50 Oral	Rabbit	1040 mg/kg	-	
	LDLo	Rat	650 mg/kg	-	
	LDLo Intraperitoneal				
	LDLo Subcutaneous	Rat	1700 mg/kg	-	

11 . Toxicological information

	Intraperitoneal			
m-phenylenebis(methylamine)	LD50 Dermal	Rabbit	2 g/kg	-
	LD50 Oral	Rat	930 mg/kg	-
2,4,6-tris(dimethylaminomethyl)phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	1200 mg/kg	-

Conclusion/Summary : Not available.

Potential chronic health effects

Chronic toxicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : No specific data.

Ingestion : Adverse symptoms may include the following:
stomach pains

Skin : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur

Eyes : Adverse symptoms may include the following:
pain
watering
redness

Target organs : Contains material which may cause damage to the following organs: skin, eye, lens or cornea.

12 . Ecological information

Environmental effects : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Water polluting material. May be harmful to the environment if released in large quantities.

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
benzyl alcohol	-	Acute LC50 460000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) - 4 to 8 weeks - 1.1 to 3.1 cm	96 hours
	-	Acute LC50 15000 ug/L	Fish - Inland silverside -	96 hours

12 . Ecological information

		Marine water	Menidia beryllina - 40 to 100 mm	
	-	Acute LC50 10000 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus - 33 to 75 mm	96 hours
3-aminomethyl-3,5,5- trimethylcyclohexylamine	-	Acute EC50 17.4 to 21.5 mg/L Fresh water	Daphnia - Water flea - Daphnia magna - <24 hours	48 hours

Conclusion/Summary : Not available.

Other ecological information

Biodegradability

Conclusion/Summary : Not available.

Other adverse effects : No known significant effects or critical hazards.

13 . Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14 . Transport information

ADG

UN number : UN1760
ADG Class : 8
Packing group : II
Proper shipping name : Corrosive liquid, n.o.s.
Label No. : 8

ADR

UN number : UN1760
ADR Class : 8
Classification code : C9
Packing group : II
Proper shipping name : Corrosive liquid, n.o.s.
Label No. : 8

IMDG

UN number : UN1760
IMDG Class : 8
Packing group : II
Proper shipping name : Corrosive liquid, n.o.s.
Emergency schedules (EmS) : F-A, S-B

Marine pollutant : P

Label no. : 8

IATA

UN number : UN1760
IATA Class : 8

14 . Transport information

Packing group : II
Proper shipping name : Corrosive liquid, n.o.s.
Label no. : 8

15 . Regulatory information

Standard for the Uniform Scheduling of Drugs and Poisons

Not regulated.

Control of Scheduled Carcinogenic Substances

Ingredient name

No listed substance

Schedule

Australia inventory (AICS) : All components are listed or exempted.

EU Classification : Xn; R20/22
C; R35
R43
N; R51/53

16 . Other information

Person who prepared the MSDS : Validated by DeSilva on 27.03.2009.

Date of previous issue : No previous validation.

✔ Indicates information that has changed from previously issued version.

Disclaimer

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy. MSDS may be obtained from the following website: www.sika.com.au

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.