

Sika Blackseal -1

Construction

Description Sika Blackseal-1 is a one component, bitumen based, caulk. The product cures to a plastic seal by evaporation of the solvent.

Uses Sika Blackseal-1 is used for weatherproof sealing of connections and sealing around pipes. The adhesion of singles, for carrying out emergency repairs on roofs, gutters, chimney's etc.

Storage and Shelf Life Stored in the original sealed containers, within the temperature range of +5°C and +25°C, this product will keep for a minimum of 12 months.

Instructions for Use

Surface Preparation & Application. Surfaces must be clean, dry, sound and free of gravel, slate and other impurities. Non porous substrates don't have to be dry. If necessary use a primer.

Technical Data (Typical)

Colour Black

Density 1.3 g/ml

Temperature Resistance -20°C - +80°C

Solids Content 85%

Skin Over Time 15 minutes

Estimated Usage Metres of joint per cartridge (width x depth)

4 x 6 mm	12.9m
6 x 6 mm	8.6m
8 x 6 mm	6.4m
12 x 8 mm	3.2m
16 x 10 mm	1.9m
20 x 12 mm	1.3m

Packaging 310ml Cartridges

Important Notes Among others not recommended for locations subject to continuous water emersion and not for PE, PP and Teflon surfaces.

Important Notification The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.



Sika Australia Pty Limited
ABN 12 001 342 329

www.sika.com.au
Tel: 1300 22 33 48