

Sika[®] Filler-107

Ready to use surface filler for use in wet areas

Description	Sika Filler-107 is a water-based, ready to use general purpose surface filler for use in wet areas.
Uses	<ul style="list-style-type: none"> • Sika Filler-107 is suitable for interior surface filling work on plaster, woven fabrics, old wallpapers, etc. in wet environments such as kitchens and bathrooms etc.
Advantages	<ul style="list-style-type: none"> • Ready to use, no mixing required. • Easy application. • High initial tack or grab on plaster and concrete. • Quick drying. • Not sensitive to moisture.
Storage and Shelf Life	12 months from date of production if stored properly in undamaged and unopened original sealed packaging, in cool and dry conditions. Protect from frost.
Instructions for Use	
Surface Preparation	All surfaces must be clean, dry, free from dust and oil.
Mixing	Sika Filler-107 is supplied ready to use, no mixing is required.
Consumption	This depends on the substrate roughness and thickness of the layer applied. As a guide, 1 litre of Sika Filler-107 can fill 1 m ² per mm thick.
Application	Sika Filler-107 can be applied with a spatula in layer thickness from 0 – 4 mm. When filling deep holes or cracks above 4 mm the filler should be applied in several layers and must be allowed to dry before each subsequent layer is applied.
Waiting Time/ Overcoatability	Drying Time: 2 to 4 hours (thicker applications might require a longer time). Paintability: 12 hours
Cleaning	Clean all tools and equipment immediately after use with water. Hardened / cured material can only be removed mechanically.

Construction



Technical Data (Typical)

Colour	Grey / blue, grey paste
Density	1.050 kg/l
Chemical Base	Filled styrene-acrylate dispersion
Solid Content	62%
Grading	D _{max} : 0.15 mm
Layer Thickness	4 mm max.
Substrate Temperature	+5°C min. / +35°C max.
Ambient Temperature	+5°C min. / +35°C max.
Packaging	500 ml plastic tube 5 l and 10 l plastic pail

Important Notification

The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.

Construction

