

Sika® Pave Fix Plus

Self setting jointing compound

Construction

Description	Ready to use, self setting jointing compound for pointing paving, pathways and patios etc.
Uses	Can be used on: <ul style="list-style-type: none">■ Patios■ Pavements■ Paths■ Flagstones■ Stone setts■ Slabs■ Cobbles■ Paving blocks■ Cubes
Advantages	<ul style="list-style-type: none">■ Simply brush in■ Self setting and self draining■ Will not wash or blow out■ Prevents weed growth and insect attack■ Shower resistant during curing■ Suitable for wide joints from 5mm upwards
Cleaning, Storage and Shelf Life	<ul style="list-style-type: none">■ Store unopened in cool, dry conditions■ Once bag is punctured or opened, contents will harden■ Shelf life - minimum 12 months in sealed, unopened bags■ Clean tools immediately after use with warm, soapy water

Instructions for Use

Surface Preparation/Application/Drying Time

Ensure all joints to be pointed with Pave Fix Plus have a minimum full depth width of 5mm and are at least 25mm deep. Joints must be dry, free from dirt, debris or weeds. Ensure the paving bedding is dry and well drained. Remove Pave Fix Plus from the packaging and cut the bag. Once punctured or opened the material must be used within 1 hour. Use Pave Fix Plus in small manageable amounts. Avoid spreading over a large area before application. Ensure material is all loose by raking through. Do not try to break up and use any small set lumps. Do not add any extra sand Using a soft broom, or hand brush for smaller areas, work Pave Fix Plus into the joints. Make sure each joint is completely filled and the material well compressed. Pave Fix Plus will start to set in 6-12 hours above 15°C in dry conditions. Allow up to 4 days for full set in temperatures between 4°C and 15°C. Contact with rain or moisture can soften product and slow the final set.

**Health & Safety
/Precautions**

- May cause sensitization by skin contact.
 - Keep out of the reach of children.
 - Avoid contact with skin.
 - Wear suitable gloves.
 - If swallowed, seek medical advice immediately and show this container or label.
 - Contains: polybutadiene.
-

Important Notification

The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.

