

# Sika® Block Paving Fix

## Easy to use, brush in joint filler

Construction

<b>Description</b>	Ready to use, moisture curing, jointing compound for paths, patios and driveways
<b>Uses</b>	Can be used on: <ul style="list-style-type: none"><li>■ Domestic driveways</li><li>■ Footpaths</li><li>■ Walkways</li></ul>
<b>Advantages</b>	<ul style="list-style-type: none"><li>■ Fast and easy to use, simply brush in and water</li><li>■ Sets hard and will not wash or blow out</li><li>■ Will not stain pavers</li><li>■ Prevents weed growth and insect attack</li><li>■ Paving may be used immediately after activation</li><li>■ Suitable for narrow joints 2mm – 4mm wide</li></ul>
<b>Cleaning, Storage and Shelf Life</b>	<ul style="list-style-type: none"><li>■ Store unopened in cool, dry conditions</li><li>■ Protect from frost</li><li>■ Clean tools immediately after use with warm soapy water</li></ul>

### Instructions for Use

#### Surface Preparation/Application/Drying Time

Ensure all joints are dry and free from dirt. Do not apply if temperatures drop below 5°C within drying period. Dry mix contents of bucket by raking through to ensure all the material is loose. Do not try to break up and use any small lumps or add any extra sand. Use in small manageable amounts and avoid spreading over a large area. Sweep material into the joints making sure each joint is completely filled. If rain is expected prior to hardening, the surface must be protected to ensure a smooth finish. Sweep up any excess material, as it can be difficult to remove once set. Thoroughly soak the joints with a garden hose, set to fine spray or a watering can fitted with a rose. Do not use a pressure washer. Ensure all joints are fully saturated. Rinse any excess material from the surface. A Block Paving Fix finished surface is safe to walk upon immediately after activation but ideally should be left to dry. Drying will usually take 1-2 days but full curing may take up to 28 days (depending on the weather conditions). Leave a minimum of 28 days before pressure washing surface.

---

**Health & Safety  
/Precautions**

- Do not breathe dust
  - Avoid contact with skin and eyes
  - Wear gloves when handling product
  - Wash hands with soap and water when work completed
  - Keep out of reach of children
- 

**Important Notification**

The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.

---

