

SikaBond[®] -TechGrip

High Strength Multipurpose Polyurethane Glue

Description	SikaBond [®] -TechGrip is a high strength multipurpose, polyurethane glue that provides a super strong bond to almost any substrate and is ideal for woodworking and project work.
Uses	SikaBond [®] -TechGrip can be used on most substrates due to its excellent adhesion. These include: <ul style="list-style-type: none">■ Wood■ Stone■ Metals■ Glass■ Ceramics■ Concrete■ Brick■ Masonry
Advantages	<ul style="list-style-type: none">■ Waterproof■ Resistant to solvents and chemicals■ Paintable with water based and solvent based paints■ High adhesion strength
Storage and Shelf Life	Store in a cool, dry place with 25C maximum condition. This material will keep for at least twelve (12) months.
Instructions for Use	
Surface Preparation	Ensure all surfaces are clean, dry, oil and dust free and that one surface is porous. (SikaBond [®] -TechGrip works best when both surfaces are porous).
Application	Apply sparingly to one surface and bring surfaces together within 15 minutes. Secure/clamp for 3-4 hours. Wipe excess away with a cloth to limit sanding after cure. Allow 24 hours for full cure. As glue will foam a little while curing, wipe off excess with a cloth to limit sanding and painting. Slightly dampen dry timber surfaces to improve bond and accelerate cure.
Cleaning	Wipe nozzle and cap of bottle after use and dispose of any unused material in accordance with local authority regulations.



Colour	Brown
Density	1.11 kg/litre approx.
Bond Strength	Tensile strength (kpa) - >80310 Shear strength (kpa) - >19867
Viscosity	6,000cps
Packaging	125g (12 cartridges per box) 500g (6 cartridges per box)
Handling Precautions	<ul style="list-style-type: none">• Avoid contact with skin and eyes.• Wear protective gloves and eye protection during work.• If skin contact occurs, wash skin thoroughly.• If in eyes, hold eyes open, flood with warm water, seek medical attention without delay.• A full Material Safety Data sheet is available from Sika on request.
Important Notification	<p>The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.</p> <p>PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.</p>

