

# S-Pipe Flashing PVC

## Prefabricated PVC pipe/vent flashing

**Product Description** The S-Pipe Flashing PVC is made of a multi-layer, synthetic roof waterproofing membrane based on premium-quality polyvinyl chloride (PVC) with inlay of glass non-woven containing ultraviolet light stabilizers and flame retardant.

**Uses** The S-Pipe Flashing PVC is used as a prefabricated part for pipe/vent flashing on Sarnafil® G/S and Sikaplan® PVC flat roof systems.

**Characteristics / Advantages**

- Outstanding resistance to weathering, including UV irradiation
- Easy and safe application
- Excellent weldability
- Lacquer coated surface
- Recyclable

### Tests

**Approvals / Standards**

- Quality management system EN ISO 9001/14001
- Reaction to fire according to EN 13501-1, class E

### Product Data

#### Form

**Appearance** Surface: smooth

**Colour** Light grey (nearest RAL 7047)  
Window grey (nearest RAL 7040)  
Lead grey (Sika colour no. 9500)  
Copper patina (Sika colour no. 6525)  
Copper brown (nearest RAL 8004)  
Traffic white (nearest RAL 9016)  
Pearl copper metallic (nearest RAL 8029)

Other colours on request

**Packaging** Depending on the order quantity and product size, the products are packaged on pallets or in cartons.

#### Storage

**Storage Conditions** S-Pipe Flashing PVC shall be stored in dry conditions.

**Shelf-Life** S-Pipe Flashing PVC does not expire during correct storage.

Construction





Art. No.	Inside diameter	Sleeve height	Flange size	Material thickness	Colour
110437	77 mm	380 mm	300 mm x 300 mm	1.5 mm	Light grey (nearest RAL 7047)
110438	82 mm				
110439	92 mm				
110440	102 mm				
110441	112 mm				
110442	122 mm				
110443	132 mm				
110444	142 mm				
110445	152 mm				
110446	167 mm				

Other diameter on request

Other colours see page 1

---

## Technical Data

---

**Material Basis** Polyvinyl chloride (PVC)

---

**Seam quality / type** High frequency welded

---

## System Information

---

**System Structure** Ancillary products: - Cap for vent pipe in various sizes  
Compatible products: - Sarnafil® G 410-types  
- Sarnafil® G 411-types  
- Sarnafil® G 476-types  
- Sarnafil® S 327-types  
- Sarnafil® S 328-types  
- Sikaplan® G / VG / VGWT / S / SG / SGmA / SGK

---

## Application Conditions / Limits

---

**Temperature** The use of S-Pipe Flashing PVC is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

---

## Installation Instructions

---

**Installation Method** According to the valid installation instructions for Sarnafil®- and Sikaplan® flat roof waterproofing membranes.

---

## Notes on Installation / Limits

Installation works to be carried out only by Sika instructed contractors for roofing.  
Temperature limits for the installation of the S-Pipe Flashing PVC:  
Substrate temperature: -30 °C min. / +60 °C max.  
Ambient temperature: -20 °C min. / +60 °C max.  
Installation of some ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5 °C. Please observe information given by Product Data Sheets.  
Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

---

<b>Value Base</b>	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.
<b>Ecology, Health and Safety Information</b>	The product does not fall within the EC-regulation of hazardous goods. As a result, a material safety data sheet following EC-Guideline 91/155 EWG is not needed to bring the product to the market, transport or use it. The product does not damage the environment when used as specified.
<b>Protective Measures</b>	Fresh air ventilation must be ensured, when working (welding) in closed rooms. Local safety regulations must be observed.
<b>Transportation Class</b>	The product is not classified as hazardous good for transport.
<b>Disposal</b>	The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.
<b>Important Notification</b>	The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms and conditions of sale. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request. PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.



**Sika Australia Pty Limited**  
ABN 12 001 342 329

**www.sika.com.au**  
Tel: 1300 22 33 48