


Fastener SB-6.3 X L



Overview	Carbon steel screw with Durocoat F coating		
Material	Hardened carbon steel		
	Thread diameter	6.3 mm	
Basic size	Drilling point Dia.	3.4 mm	
	Head & Drive type	Flat head ,drive T30	
Corrosion resistance	15 cycles Kesternich test		
Approval	FM approval for Chinese Application		
	Article No.	Size	Package
	6.500.334	6.3x 32 mm	500Pcs
	6.500.335	6.3x 50 mm	500Pcs
	6.500.336	6.3x 75 mm	500Pcs
	6.500.337	6.3x 100 mm	500Pcs
Specification	6.500.338	6.3x 120 mm	500Pcs
	6.500.339	6.3x 140 mm	500Pcs
	6.500.340	6.3x 160 mm	250Pcs
	6.500.341	6.3x 180 mm	250Pcs
	6.500.342	6.3x 200 mm	250Pcs
	6.500.343	6.3x 230 mm	250Pcs
	6.500.344	6.3x 250 mm	250Pcs
Application	On qualified substrate, including concrete, steel deck, wood, etc.; Normal environment, humidity below 70% and no chemical condition.		

The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.

Sarnafil®

Sika®

Sika Australia Pty Limited
ABN 12 001 342 329

www.sika.com.au
Tel: 1300 22 33 48