

Sarnafil® S-Welding Cord

Construction

Overview	Sarnafil S-Welding Cord is a hot air weldable PVC cord.	
Properties	Material	PVC dry blend
	Colour	Light grey
	Dimension (mm)	Diameter – 4
Application	Sarnafil S-Welding Cord is welded to the membrane using special welding nozzle along S-U Bar to resist pull forces (like wind up-lift) towards roof centre as reinforced perimeter fixation. It helps to distribute the load evenly and prevent slippage of the membrane.	
Packaging	300 lineal metres	

Important Notification

The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.



Sika Australia Pty Limited
ABN 12 001 342 329

www.sika.com.au
Tel: 1300 22 33 48

Sarnafil® S-Welding Cord
Page 1 of 1

Sarnafil®