

Sarnafil® Walkway Pad

Construction

Overview	Sarnafil walkway pad is a durable, traffic bearing, head weldable rooftop walkway pad used on a Sarnafil roof system.
Material	<p>Sarnafil walkway pads are injection moulded. The material formula meets the same high standards for raw materials and durability met by time-tested Sarnafil G/S/F roofing membrane.</p> <p>Size 600 x 600 mm non-slip walking surface with a 75 mm weld tab at each end</p> <p>Thickness 7 mm (including the 3 mm traction profiles)</p> <p>Colour Dark Grey</p> <p>Weight 2.3 kg per walkway pad</p>
Properties	<ul style="list-style-type: none"> • A herringbone pattern of 3 mm high traction profiles provides a durable walking surface and fast water runoff • Interlocking alignment tabs • Weld tabs for making lap splices with almost any welder – right over the existing Sarnafil G/S/F roof • Water runoff channels in all direction on the underside • Installation is fast and easy. The pads require no underlayment
Packaging	1 pad

Important Notification

The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.

