

SikaForce[®]-7010

Hardener for two component polyurethane adhesive

Technical Product Data:

Chemical Base	Isocyanate derivatives
Colour (CQP ¹⁾ 001-1)	Brown
Solids content	100%
Density ²⁾ (CQP 006-5)	1.2 g/cm ³ approx
Viscosity ²⁾ (CQP 538-2) Brookfield RVT 2/50	250 mPa.s
Shelf Life (storage between 10 and 30°C)	9 months

¹⁾ CQP = Corporate Quality Procedure

²⁾ 23°C / 50% r.h.

Description

SikaForce[®]-7010 is a solvent-free brown hardener liquid of low viscosity. It is designed to be used in combination with SikaForce[®] adhesive systems.

This product is manufactured in accordance with ISO 9001 and ISO 14001 quality assurance systems and the responsible care program.

Product Benefits

- Thin liquid
- Low vapour pressure

Areas of application

SikaForce[®]-7010 is a hardener for two component SikaForce[®] polyurethane adhesive systems. Refer to the Product Data Sheet of the adhesive to see the fit for use. This product is suitable for professional experienced users only.

Industry



Cleaning

Un-cured hardener on tools and application equipment can be removed with SikaForce®-7260 Cleaner.

Cured hardener can only be removed mechanically.

Storage Conditions

To be stored between 10°C and 30°C in a dry place. Do not expose to direct sunlight.

After opening of the packaging, the contents should be protected against atmospheric humidity.

Further information

The following publications are available on request:

- Material Safety Data Sheet.

Packaging Information

Can	5 kg
Drum	250 kg

Value Bases

All technical data stated in this Product Data Sheet is based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Important

For information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety related data.

Note:

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Australian version of the Product Data Sheet for the product concerned, copies of which will be supplied on request.

