

# Sika<sup>®</sup> Teak Cleaner, Sika<sup>®</sup> Teak Brightener and Sika<sup>®</sup> Teak Oil

## Sika<sup>®</sup> Teak Deck Maintenance System

### Technical Product Data:

	Sika Teak Cleaner	Sika Teak Brightener	Sika Teak Oil
Chemical Base	Alkaline tenside solution	Oxalic based composition	Solvent based oil composition
Consistency	Colourless liquid	Colourless liquid with pleasant sweet odour	Amber liquid with solvent odour
Use	Cleaning of Teak and similar wood	Brightener to remove surface oxidation products (graying), stains or mildew from Teak and similar wood	Protection oil to bring out the natural grain and colour of the wood
Density (at 20°C)	1.02	1.01	0.81
Application temperature	10°C to 30°C		
Shelf life and storage	5 years in non opened bottles		

#### Description:

The Sika Teak Deck Maintenance System consists of three products:

- Sika Teak Cleaner
- Sika Teak Brightener
- Sika Teak Oil

These products have been developed to maintain a perfect compatibility of a teak deck which has been bonded and sealed with Sika products.

#### Product benefits:

- Quick and easy to use
- No raise of the wood grain
- Good UV protection through the Sika Teak Oil
- Improves resistance against mildew growth

#### Areas of Application:

The products are used to clean, refresh and protect a teak deck on boats, ships and yachts.

This product is suitable for professional experienced users only.

**Application:***Sika Teak Cleaner*

Pour onto the dry deck and spread out with a brush or scrub pad. Allow to react for two to three minutes, then lightly scrub in the direction of the wood grain. Rinse with plenty of fresh water. Extremely dirty or grey wood may require a second application.

Note: Do not use the product without rinsing with fresh water.

*Sika Teak Brightener*

After cleaning the wood with Sika Teak Cleaner pour Sika Teak Brightener onto the wood and spread with a brush or scrub pad. Leave it for about 5 minutes, then scrub slightly in the direction of the wood grain.

Mildewed areas may require scrubbing with a coarse brush or scrub pad. Rinse with fresh water. Extremely stained or grey surfaces may require a second application.

*Sika Teak Oil*

Wood must be prepared using Sika Teak Cleaner and Sika Teak Brightener. Apply Sika Teak Oil on the dry deck with a brush or cloth. Allow to remain on the surface for 2-3 minutes. Wipe off the excess of oil with a clean lint free cloth.

Extremely porous wood may require a second or even a third application. Wood is properly oiled, when excess oil stays on the surface of the wood, without being absorbed and requires a wipe off. Minimum drying time is 6 hours.

**Note:** Splashes of these products on cover fittings and other parts have to be cleaned off immediately.

*Important:*

These products have been extensively tested in conjunction with Sikaflex®-290DC teak deck caulking material. Correctly applied, there is no negative effect on the joints. However, in high concentration the products contain active chemicals which may impair the sealant when used in prolonged contact with the undiluted concentrated Teak Maintenance products. Therefore strictly observe the application recommendations.

**Further Information:**

Copies of the following publications are available on request:

- Material Safety Data Sheets
- Leaflet "Teak Deck Maintenance System"
- Teak Deck Maintenance recommendation

**Packaging information:**

Plastic bottle	1L
----------------	----

**Value Bases:**

All technical data stated in this Technical Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

**Health and Safety Information:**

For information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Material Safety Data Sheets containing physical, ecological, toxicological and other safety related data.

**Note:**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Australian version of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

