

# SikaForce®-7260 Cleaner

Liquid for cleaning of tools and application equipment

## Technical Product Data

Chemical Base	Dipropylene glycol ether
Colour (CQP <sup>1)</sup> 001-1)	Transparent
Density <sup>2)</sup> (CQP 006-6) <sup>2)</sup>	0.96 g/cm <sup>3</sup>
Viscosity <sup>2)</sup>	4 mPa.s approx.
Vapour Pressure	0.4 mm Hg/25°C approx.
Boiling point	190°C approx.
Flash point	80°C approx.
Shelf life (storage between 10 and 30°C in tightly closed packaging)	12 months

<sup>1)</sup> CQP = Corporate Quality Procedures

<sup>2)</sup> +23°C / 50% r.h.

### Description:

High boiling liquid for cleaning of non-cured one and two component polyurethane products. This product is manufactured in accordance with ISO 9001 and ISO 14001 quality assurance systems.

### Product Benefits:

- Not classified
- Neutralises the isocyanate groups in PUR products.

### Areas of Application:

Cleaning of tools and application equipment used for one and two component polyurethane products. Cleaning and flushing of one and two component application equipment.

Industry



**Directions for use:**

Removal of one and two component polyurethane products should take place while they are still liquid.

When using SikaForce®-7260 Cleaner at temperatures above 30°C, ventilation is recommended.

Clean tools with SikaForce®-7260 Cleaner using a brush, if necessary after immersion. In two component equipment, flushing with recirculation is recommended.

By mixing of a lot of polyurethane with a small amount of SikaForce®-7260 Cleaner, the mixture may develop heat. Consequently, there should always be an excess of SikaForce®-7260 Cleaner.

Apart from cleaning of non-cured polyurethane products, SikaForce®-7260 Cleaner may also be advantageously used for removing other uncured products. Tests should be made to find its suitability.

**Storage Conditions:**

Keep the packing tightly closed and store in a well ventilated storage room.

**Further Information:**

The following publications are available on request:  
- Material Safety Data Sheet

**Packaging:**

Drum	200 kg
------	--------

**Important:**

For information and advice on the safe handling, storage and disposal of chemical products users should refer to the relevant Material Safety Data Sheet(s) containing physical, ecological, toxicological and other safety related data for the appropriate type of substance.

**Note:**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Australian version of the Product Data Sheet for the product concerned, copies of which will be supplied on request.

