

Sika® Remover-208

Cleaning agent for surface preparation and removal of uncured adhesive and sealants

Technical Product Data:

Chemical base	Organic solvent
Colour	Colourless, clear
Density (CQP 006-3 / ISO 2811-1)	0.8 kg/l approx.
Flash point (CQP 007-1 / ISO 13736)	24°C
Application temperature	5 - 40°C
Application	Wipe on, wipe off with lint free paper towel
Storage	Store in sealed container in a cool dry place below 25°C
Shelf life	24 months

¹⁾ CQP = Corporate Quality Procedure

²⁾ 23°C / 50% r.h.

³⁾ When applied at other temperatures, contact Technical Service Department of Sika Industry.

Description:

Sika® Remover-208 is used to remove traces of Sikaflex® products as well as for cleaning painted substrates.

Sika® Remover-208 is manufactured in accordance with the ISO 9001/14001 quality assurance system and with the responsible care program.

Areas of application:

Sikaflex® Remover-208 can be used to remove excess uncured Sikaflex® adhesive or sealant from application tools or from soiled surfaces.

Sika® Remover-208 can also be used for pre-cleaning strongly contaminated non-porous substrates.

Sika® Remover-208 can be used to clean painted surfaces prior to bonding.

This product is suitable for professional experienced users only. Test with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

Method of application:

Removal of uncured adhesive
Remove the bulk of the Sikaflex® residue with a knife or spatula. Moisten a rag or towel with Sika® Remover-208 and wipe off the remaining adhesive or sealant.

Surface cleaning

Wipe painted surfaces with a moistened rag or towel with Sika® Remover-208. Wet the paper towel with solvent by pouring the liquid onto the cloth. Never dip the paper towel into the cleaner as it may contaminate it. Wipe the surface with a wetted paper towel. Use fresh paper towels regularly in order to retain the cleansing power. Before the solvent dries on the surface (evaporates), wipe it off with a different clean, dry paper towel.

Repeat the last two steps until no contaminants show up on a white paper towel.

Do not use on sensitive surfaces such as fresh paints.

Tightly reseal container immediately after each use.

Industry



Important note:

Sika® Remover-208 must not be used to clean soiled skin.

Further information:

Copies of the following publications are available on request:

- Material Safety Data Sheet

Packaging information:

Can	250 ml
	1000 ml

Health and Safety Information:

For information and advice on the safe handling, storage and disposal of chemical products, users should refer to the current Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Note:

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Australian version of the Product Data Sheet for the product concerned, copies of which will be supplied on request.

